



KRYLON® COLORmaxx™ BRUSH-ON

General Purpose

Gloss, Flat, Satin

PRODUCT DESCRIPTION	APPLICATION	CAUTIONS
COLORmaxx™ provides premium coverage with exceptional smooth and durable water-based paint for indoor and outdoor projects.	After opening, stir thoroughly. This product can be applied over latex primer for additional coverage. Use a quality nylon or polyester brush or roller cover for latex paints. After use, clean excess paint, tools and accessories with warm, soapy water. Wash hands after using.	CONTAINS CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.
PAINTING CONDITIONS	CHARACTERISTICS	
Use outdoors or in a well-ventilated area. For best results, use when air & surface temperature is 50°F (10°C) to 90°F (32°C) & humidity is below 75%.	Available sheens: Gloss, Satin, Flat Coverage: Up to 100 square feet on a solid non-porous surface.	
SURFACE PREPARATION		PERFORMANCE TESTING
WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Surface should be clean, dull & dry. Remove loose paint, rust, dirt, grease and oil. To improve adhesion, sand glossy or rough surfaces until smooth.	Drying Time, @ 77°F, 50% RH: <i>Drying time and recoat times are temperature, humidity, and film thickness dependent.</i> Touch: 1 Hour Recoat: Allow to dry overnight before recoating. Vehicle Type: Acrylic Latex Finishes: Gloss, Flat, Satin Net Wt.: 128 FL OZ. / 3.78L Volume Solids: 30-40% Weight Solids: 30-55%	Technical data furnished herein is accurate and true to the best of our knowledge. However, no guarantee of accuracy is expressed or implied. We assume no responsibility or liability as a result of purchase, coverage, application or injuries resulting in misuse. To contact us call 1-800-247-3268 or ask@krylon.com.