Contractor Series LED A19 Lamps

11,000 Hours Life



Rated up to 11,000 hours at 70% lumen maintenance, Contractor Series LED A19 lamps offer years of service and reduce energy and maintenance costs. Contractor Series LED A19 lamps are environmentally preferred products. They are RoHS compliant and contain no mercury, lead or other hazardous materials. They emit no UV or IR radiation. A CRI of 80+ ensures good color definition. Available in warm white 2700K CCT and bright white 5000K CCT, these lamps offer a great value where a non-dimmable, semidirectional lamp is appropriate in both homes and businesses.

Key Features & Benefits

- UV and IR free
- Mercury and lead free
- RoHS compliant
- Available in 2700K & 5000K color temperatures
- Rated life: up to 11,000 hours (L₇₀)
 Suitable for indoor environments
 - Reduces energy consumption up to 86%
 - Lasts up to 11 times longer than incandescent lamps
 - No warm-up time, instant-on with full light output and stable color









Product Offering

Ordering	Color	Typical
Abbreviation	Temperature	Lumens
6 Watt A-line	2700K & 5000K	450
8.5 Watt A-line	2700K & 5000K	800
12 Watt A-line	2700K & 5000K	1100
14 Watt A-line	2700K & 5000K	1500

Application Information

Applications

- Downlights
- Pendant fixtures
- Table lamps
- Wall sconces

Market Segments

- Healthcare
- Hospitality
- Residential
- Retail

Application Notes

- 1. Operating temperature range between -20°C and +45°C (-4°F and +113°F)
- 2. Not for use with emergency light fixtures or exit lights
- 3. Not for use in totally enclosed luminaires
- 4. Suitable for indoor environments
- 5. Not intended for use with dimmers

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, please see www.sylvania.com/fcc15b.



Specification Data

Catalog #	Туре
Project	
Comments	
Prepared by	

Ordering Information

					Input	Average		Typical				
Item	Ordering	Wattage	Base		Voltage	Rated		Lumens		Power	Bulb	ENERGY
Number	Abbreviation	(W)	Type	Replaces	(V)	Life (hrs.)	CCT	(lm)	CRI	Factor	Finish	STAR®
74076	LED6A19/F/827/10YV/RP	6	Medium	40W A19	120	11,000	2700K	450	80	0.5	Frosted	N/A
74077	LED6A19/F/827/10YV/RP2	6	Medium	40W A19	120	11,000	2700K	450	80	0.5	Frosted	N/A
74079	LED6A19/F/827/10YV/RP4	6	Medium	40W A19	120	11,000	2700K	450	80	0.5	Frosted	N/A
74080	LED6A19/F/850/10YV/RP	6	Medium	40W A19	120	11,000	5000K	450	80	0.5	Frosted	N/A
74081	LED6A19/F/850/10YV/RP2	6	Medium	40W A19	120	11,000	5000K	450	80	0.5	Frosted	N/A
74084	LED6A19/F/850/10YV/RP4	6	Medium	40W A19	120	11,000	5000K	450	80	0.5	Frosted	N/A
73885	LED8.5A19/F/827/10YV/RP	8.5	Medium	60W A19	120	11,000	2700K	800	80	0.5	Frosted	N/A
73886	LED8.5A19/F/827/10YV/RP2	8.5	Medium	60W A19	120	11,000	2700K	800	80	0.5	Frosted	N/A
73888	LED8.5A19/F/827/10YV/RP4	8.5	Medium	60W A19	120	11,000	2700K	800	80	0.5	Frosted	N/A
79281	LED8.5A19/F/850/10YV/RP	8.5	Medium	60W A19	120	11,000	5000K	800	80	0.5	Frosted	N/A
79282	LED8.5A19/F/850/10YV/RP2	8.5	Medium	60W A19	120	11,000	5000K	800	80	0.5	Frosted	N/A
79284	LED8.5A19/F/850/10YV/RP4	8.5	Medium	60W A19	120	11,000	5000K	800	80	0.5	Frosted	N/A
79291	LED12A19F82710YVRP	12	Medium	75W A19	120	11,000	2700K	1100	80	0.5	Frosted	N/A
79293	LED12A19F85010YVRP	12	Medium	75W A19	120	11,000	5000K	1100	80	0.5	Frosted	N/A
79292	LED14A19F82710YVRP	14	Medium	100W A19	120	11,000	2700K	1500	80	0.5	Frosted	N/A
79294	LED14A19F85010YVRP	14	Medium	100W A19	120	11,000	5000K	1500	80	0.5	Frosted	N/A

Ordering Guide

LED	6	A19	/	F	1	8	27	/	10YV	1	RP
LED	Wattage:	Lamp Type:		Frosted		CRI	CCT		11,000 hours life		Retail Package
Lamps	6	A19				8=80+	27=2700K				RP2: 2 lamp Retail Package
							50=5000K				RP4: 4 lamp Retail Package

Lamp Dimensions

	(A) MOL inches (mm)	(B) Diameter inches (mm)
LED6A19	4.4 (112)	2.36 (60)
LED8.5A19	4.4 (112)	2.36 (60)
LED12A19	4.3 (109)	2.36 (60)
LED14A19	4.3 (109)	2.36 (60)

Energy Savings

Basic Product	LED	LED	Similar	Incandescent	Incandescent	Watts	Energy	LED Life vs.
Description	Life (hrs.)	Lumens	Incandescent	Lumens	Life (hrs.)	Saved	Savings*	Incandescent
LED6A19	11,000	450	40W A19	465	1500	34	\$41.14	7.3x
LED8.5A19	11,000	800	60W A19	850	1000	51.5	\$61.71	11x
LED12A19	11,000	1100	75W A19	1170	750	63	\$76.23	14.6x
LED14A19	11,000	1500	100W A19	1600	750	86	\$104.06	14.6x

^{*}Energy savings over life of lamp calculated at \$0.11/kWh

LEDVANCE LLC 200 Ballardvale Street Wilmington, MA 01887 USA Phone 1-800-LIGHTBULB (1-800-544-4828) www.sylvania.com

SYLVANIA and LEDVANCE are registered trademarks.

All other trademarks are those of their respective owners.

Product Licensee of Trademark SYLVANIA in General Lighting.

Specifications subject to change without notice.





