



Valspar® Exterior Latex Field Marking Paint

No. 655 series

GENERAL DESCRIPTION

A fast-drying latex flat paint designed to mark athletic fields of natural grass, synthetic turf, clay or concrete. May be reduced to up to 1:1 with water. Formulated for professional painter use in residential, commercial, institutional and industrial applications.

RECOMMENDED USES

Designed for field marking and lining on athletic-field surfaces of natural grass, synthetic turf, clay or concrete. Use for marking fields, temporary parking or when surface striping or marking is desired. This product is for exterior-field use only.

SURFACE PREPARATION

Cut grass to desired level before painting. If grass is very dry, irrigate field and allow surface water to be absorbed before painting. Field should be dry, without any standing water or dew. Surface should be clear of debris.

APPLICATION

Use a paint paddle or mixing blade to stir paint thoroughly, bringing pigments to the top of the can. Intermix all cans of the same color, paint should be smooth, with uniform color and no air bubbles. This product is designed for application by airless, line-marking equipment, but may be applied by brush, roller or spray.

Airless Spray: Start with 1700–2000 PSI and 0.015 to 0.021 tip.

Roller: 3/8" or 3/4" nap (10 or 19 mm nap) synthetic roller cover.

Line-striping equipment: See manufacturer's specifications for proper tip size and pressure settings.

CLEANUP AND DISPOSAL

Do not freeze. Clean up with warm, soapy water. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

CAUTIONS

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. **Use only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. **WARNING:** This product contains a chemical known to the State of California to cause cancer.

First Aid: Eye Contact: Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.*

*Call poison control center, hospital emergency room or physician immediately.

UCL 3.1

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE: 1-888-345-5732

PRODUCT SPECIFICATIONS

Vehicle Type: Vinyl Acetate Ethylene Copolymer
Pigment Type: Titanium dioxide
Viscosity: 90–98 Krebs Units
Gloss: 0–5 units @ 85° angle
VOC (g/L): less than 50 g/L
VOC (lbs./gal.): 0.38
Volume Solids: 16%
Weight Solids: 30%
Weight Per Gallon: 9.96 lbs./gal
Practical Coverage: Up to 3000 sq. ft. per 5-gallons, depending on surface porosity. Approximately 5000–6000 linear ft. at 4" wide stripe per 5-gallon pail. Thin as needed, up to 1:1 ratio with clean water.
Recommended Film Thickness:
2.7 mil Wet 0.4 mil Dry
Dry Time @ 77 °F and 50% Relative Humidity
To The Touch: 30 minutes
Recoat: 1 hour
Application Temperature: 50–90 °F (10–32 °C)

COMPOSITION

	Base and Fill Levels
5 gallon pails	(oz./gal.)
White	128
Clear Base (656)	116

REGULATORY COMPLIANCE

Current as of: 8/18/2014	
SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

LIMITED WARRANTY

If this product is applied in accordance with label directions to a properly prepared, sound surface, and it fails to perform due to a deficiency in the product, return the product to the store with proof of purchase for additional product of equal value or a full refund. **THIS WARRANTY EXCLUDES LABOR COSTS AND ANY OTHER INCIDENTAL OR CONSEQUENTIAL DAMAGES.** This warranty gives you specific rights, and you may also have other rights that vary from state to state.

8725 W. Higgins Rd., Chicago, IL 60631
877.825.7727
valsparpaint.com
Revised: 8/18/14
Version: 655B